

Galvanized Coil & Sheet Specification

Items	Description
<u>QUALITIES</u>	DX51D, A526, FE PO2G, SGCC AND CQ
<u>STANDARDS</u>	EN10142-01, ASTM A653/94, EN 10142/91 AND JIS-G3302/94
<u>SPANGLE TYPE</u>	NORMAL ACCORDING TO EN10142/91, EN 10142/00
<u>SURFACE APPEARANCE QUALITY</u>	AS COATED
<u>DIMENSIONAL</u>	THICKNESS: 0.5 mm – 1.8 MM
	WIDTH: 1000 mm – 1250 MM
	INSIDE DIAMETER : 508 AND/OR 610 MM
<u>SURFACE PROTECTION</u>	OILED / UNOILED (SURFACE OILD WITH 0.2,0.5,1,AND 2 GR/M2
<u>ZINC COATING MASS</u>	ACC TO EN 10142 FROM 100 GR/M2 TO 275 GR/M2
<u>PASSIVATION</u>	CHROMATED
<u>PACKING</u>	TARRED PAPER WRAPPING – PLASTIC – CARTON FOR EDGE PROTECTION – STEEL FLANGED CROWN FOR PROTECTION OF COIL CROWN – STEEL SHEET FOR OUTSIDE PROTECTION – SERRATED COLLARS FOR OUTSIDE EDGE – INSIDE COLLARS BOUND WITH 3 CIRCUMFERENTIAL AND 5 RADIAL STRAPS. WOODEN PALLET FASTENED WITH 3 STRAPS.